MAXIGEAR EP-X 85W-90 LS

High Quality Limited Slip Automotive Gear Oil

Description

Automotive gear oil with limited slip quality, produced by using high quality advanced base oils and a balanced and advanced additives package.

Applications

Can be used in passenger car, heavy duty vehicle and off-road vehicle gear boxes and locked differentials requiring limited slip quality.

Benefits

- The limited slip feature provides perfect lubrication in all locked gear boxes requiring this quality, and working at high temperatures and heavy loads.
- Prevents noise in locked differentials.
- Provides a high level of protection for all differentials and gear boxes with GL-5 performance level.
- Facilitates starting at low temperatures, and prevents wear.
- Extends the oil change intervals.
- Provides excellent protection at high temperatures to occur in transmissions continuously operating under limited slip conditions.

Performance

Tel.: +7 771 500 90 90

API GL-5, ZF TE-ML 05C-12C-21C

Typical Specifications*

SAE Viscosity Grade		85W-90
Density, 15 °C, kg/liter	ASTM D4052	0,900
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm²/s	ASTM D445	160
Viscosity, 100 °C, mm²/s		15,5
Viscosity Index	ASTM D2270	100
Pour Point, °C	ASTM D97	-24

* Values shown may differ between productions.

