

MAXIMA 0W-20

Fully Synthetic Motor Oil

Description

Maxima 0W-20 is produced based on synthetic lubrication technology to fulfill expectation of new high technology engines.

Applications

Maxima 0W-20 is recommended for the vehicles requiring special lubricants, designed specifically for improved engine performance, increased fuel efficiency and engine deposits.

Benefits

- Extends drain intervals far beyond those recommended for conventional oils.
- Maximizes energy efficiency for improved fuel economy.
- Maxima 0W-20 motor oil provides outstanding anti-wear protection with excellent viscosity film strength.
- Low-viscosity lubrication ensures improved engine performance through a wide range of temperatures. Especially in cold weather, quick flow to critical parts will result in faster starts and better overall engine protection.

Performance

API SN/CF, ACEA A1/B1

Typical Specifications*

| | | |
|---------------------------------------|------------|-------|
| SAE Viscosity Grade | | 0W-20 |
| Density, 15 °C, kg/liter | ASTM D4052 | 0,844 |
| Flash Point, COC, °C | ASTM D92 | 228 |
| Viscosity, 40 °C, mm ² /s | ASTM D445 | 45,5 |
| Viscosity, 100 °C, mm ² /s | | 8,80 |
| Viscosity Index | ASTM D2270 | 177 |
| Pour Point, °C | ASTM D97 | -30 |

* Values shown may differ between productions.

