

MAXIMA AUTO LPG 5W-30

Synthetic Motor Oil for Next-Generation LPG Fueled Engines

Description

It is a synthetic motor oil formulated specifically for LPG vehicles, which is produced by adding high-performance additives to high technology synthetic base oils.

Applications

It can be used in LPG-reformed passenger cars and light commercial vehicles with next-generation engines, and in vehicles with factory-installed LPG fuel systems.

Benefits

- Prevents temperature caused by overheating in engines operating with LPG.
- Resistant to high engine temperature thanks to its synthetic formula.
- Its special formula provides reduction control with less evaporation loss. It minimizes the abrasion by reducing the friction during the start-up.
- Extends engine life by providing superior protection against wear and corrosion.
- Increases engine efficiency and provides high engine power.
- Provides faster start-up and protection.

Performance

API SL/CF ACEA A3/B4

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,850
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	67.2
Viscosity, 100 °C, mm ² /s		11,90
Viscosity Index	ASTM D2270	160
Pour Point, °C	ASTM D97	-41

* Values shown may differ between productions.

