

# MAXIMA CX 5W-30

Fully Synthetic Motor Oil for the Vehicles with Diesel Particulate Filter

## Description

Maxima CX 5W-30, an engine oil formulated with the synthetic base oils and special additives, produced for the vehicles with emission reducing systems containing DPF and SCR.

## Applications

Maxima CX 5W-30 can be used in the gasoline vehicles with catalytic convertor and diesel passenger and light commercial vehicles equipped with the exhaust systems containing DPF and SCR, requiring engine oil at the ACEA C2 or C3 performance level.

## Benefits

- Provides product optimization in the large vehicle fleets consisting of different brands.
- Provides high engine performance.
- Extends the life of the exhaust emission systems.
- Protects the environment by providing contribution to the production of low emission.
- Ensures that engine remains clean by reducing the formation of residue and sediment.
- Helps with fuel economy.

## Performance

API SN, ACEA C2, C3, Fiat 9.55535-S1, MB 229.31

## Typical Specifications\*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,849
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm <sup>2</sup> /s		74,7
Viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	12,40
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-33

\* Values shown may differ between productions.

