

MAXIMA GA 5W-30

Fully Synthetic Motor Oil

Description

Maxima GA 5W-30 is a fully synthetic engine oil developed for diesel and gasoline engines with particulate filter. It is recommended in particular for use in Opel, BMW and Mercedes-Benz vehicles which require the use of engine oils produced with low-ash technology. It has official GM Dexos2™ approval.

Applications

Recommended for high performance gasoline and diesel passenger cars and light commercial vehicles. It is particularly well suited for Opel cars where Dexos2™ performance level is a requirement.

Benefits

- The low ash, phosphorus and sulphur contents extend the life of exhaust systems, and protects the environment.
- It keeps the engine clean, decreases friction, and extends the life of the engine.
- It provides excellent wear control, in particular during starts.
- It provides fuel savings up to 3%.

Performance

API SN, ACEA C3, GM Dexos2, MB 229.51/229.52, VW 502.00/505.00/505.01

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,848
Flash Point, COC, °C	ASTM D92	228
Viscosity, 40 °C, mm ² /s	ASTM D445	60,36
Viscosity, 100 °C, mm ² /s		11,20
Viscosity Index	ASTM D2270	181
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.

