

MAXIMA K 5W-30

Full-Synthetic Gasoline Motor Oil

Description

This is new-generation motor oil, which is formulated with synthetic base oils and special additives, and which produced for vehicle motors containing DPF and SCR and having emission-reducing systems.

Applications

Maxima K 5W-30 for diesel passenger and light commercial vehicle motors equipped with DPF and SCR exhaust emission systems demanding motor oil with an ACEA C2 or C3 performance level and gasoline vehicle motors with catalytic converters. This is specially developed for KIA branded vehicles.

Benefits

- Ensures high motor performance.
- Extends the life of the exhaust emission systems.
- Contributes to the low emission production and protects the environment.
- Reduces the generation of the residue and dropping and ensures the motor to remain clean.
- Helps the fuel saving.

Performance

ACEA C2/C3, API SN

Typical Specifications*

SAE Viscosity Grade		5W30
Density, 15 °C, kg/liter	ASTM D4052	0,860
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm ² /s	ASTM D445	74,7
Viscosity, 100 °C, mm ² /s		12,40
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.

