

MAXIMA PG 0W-30

Fully Synthetic Motor Oil for New Generation PSA Group Vehicles

Description

Maxima PG 0W-30, an engine oil formulated with the synthetic base oils and special additives, produced for especially PSA Group Vehicles with emission reducing systems that equipped with DPF and SCR.

Applications

Suitable for PSA Group Vehicles with “BlueHDI” technology engine containing SCR. Also suitable for gasoline and diesel engines of PSA Group Vehicles with or without DPF. Maxima PG 0W-30 can be used in vehicle engines that require ACEA C3 performance level.

Benefits

- Extends the life of aftertreatment systems.
- Provides longer engine life with high anti-wear properties.
- Excellent lubrication even at low temperatures.
- Contribution to the fuel economy by reducing friction.
- Helps protect the environment by reducing emissions.
- Reduces sludge and deposits by excellent oxidation resistance.

Performance

ACEA C2-12, Fiat 9.55535-DS, PSA B71 2312

Typical Specifications*

SAE Viscosity Grade		0W-30
Density, 15 °C, kg/liter	ASTM D4052	0,840
Flash Point, COC, °C	ASTM D92	240
Viscosity, 40 °C, mm ² /s	ASTM D445	54,40
Viscosity, 100 °C, mm ² /s		9,90
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-48

* Values shown may differ between productions.