

maximarine CYL SERIES

Description

Maximarine CYL Series is a new generation cylinder lubricating oil that is produced with highly refined base oils and special additives, and meets the requirements of IMO 2020.

Applications

It is used to lubricate the cylinders of new generation two-stroke marine engines operating under heavy mechanical load and thermal conditions, and using low or high sulfur fuel.

Benefits

- It is designed for different needs and accommodates a wide range of applications.
- It keeps the wear on cylinders and liners under control.
- It prevents the formation of deposits and sediments in the pistons and rings.
- It provides a long service life at different ambient temperatures.

Typical Specifications*

		MAXIMARINE CYL 20	MAXIMARINE CYL 25	MAXIMARINE CYL 40	MAXIMARINE CYL 55	MAXIMARINE CYL 70	MAXIMARINE CYL 100
SAE Viscosity Grade		50	50	50	50	50	50
Density, 15 °C, kg/liter	ASTM D4052	0,900	0,900	0,934	0,927	0,935	0,952
Flash Point COC, °C	ASTM D92	270	270	270	270	270	270
Viscosity, 100 °C, mm ² /s	ASTM D445	19	19	19	19	19	19
Viscosity Index	ASTM D2270	98	98	98	98	98	98
T.B.N., mgKOH/gr	ASTM D2896	20	25	40	55	70	100
Pour Point, °C	ASTM D97	-15	-15	-15	-15	-15	-15

* Values shown may differ between productions.

