

MAXIMUS TURBO DIESEL EXTRA 15W-40

Heavy Duty Diesel Engine Oil

Description

Long life diesel engine oil, equivalent to super high performance diesel (SHPD) engine oil providing excellent performance in diesel engines operating with low and high sulfur fuels.

Applications

It is recommended for all heavy-duty vehicles, buses, trucks, construction equipment, and generators having diesel engines, especially turbocharged and low-emission diesel engines.

Benefits

- Prevents the engine using fuel with high sulfur content by its high TBN value.
- Reduces wear at high speeds and temperatures.
- Increases combustion efficiency by keeping engine clean.
- Extends spare parts life.

Performance

API CI-4, ACEA E7-16, JASO DH-1, CAT ECF-1a, Cummins CES 20077/78, Detroit Diesel DDC 93K215, Deutz DQC-III, Global DHD-1, Mack EO-N, MAN M3275, MB-Approval 228.3, MTU Type 2, Renault Trucks RV-I/RLD-2, Volvo VDS-3

Typical Specifications*

SAE Viscosity Grade		15W-40
Density, 15 °C, kg/liter	ASTM D4052	0,886
Flash Point, COC, °C	ASTM D92	240
Viscosity, 40 °C, mm ² /s	ASTM D445	114
Viscosity, 100 °C, mm ² /s		15
Viscosity Index	ASTM D2270	139
Pour Point, °C	ASTM D97	-30

* Values shown may differ between productions.