

# MAXIMUS TURBO DIESEL S 15W-40

Heavy Duty Diesel Engine Oil

## Description

High quality diesel engine oil ensuring high performance in all diesel engines operating under severe conditions by its superior protection and long life characteristics.

## Applications

Recommended for trucks, buses, construction machines, agricultural machines and generators with diesel engine, especially with turbocharged engine.

## Benefits

- Provides excellent performance for highway and construction use.
- Reduces pressure drop and evaporation loss.
- Prevents excess wear at cold start.
- Enables excellent results when used with fuels containing high level of sulfur.
- Keeps the engine clean and reduces friction.

## Performance

API CG-4/CF-4/CF/SH/SG, ACEA E2, MB 228.1

## Typical Specifications\*

|                                       |            |        |
|---------------------------------------|------------|--------|
| SAE Viscosity Grade                   |            | 15W-40 |
| Density, 15 °C, kg/liter              | ASTM D4052 | 0,884  |
| Flash Point, COC, °C                  | ASTM D92   | 240    |
| Viscosity, 40 °C, mm <sup>2</sup> /s  | ASTM D445  | 111    |
| Viscosity, 100 °C, mm <sup>2</sup> /s |            | 15,30  |
| Viscosity Index                       | ASTM D2270 | 145    |
| Pour Point, °C                        | ASTM D97   | -30    |

\* Values shown may differ between productions.