

ÖZEL ANTİFRİZ

Ethylene Glycol Based Special Antifreeze

Description

It is a high quality coolant antifreeze with long service life, containing special additives in the ethylene base substance. It does not contain nitrites, amine and phosphate.

Applications

It can be used in all cooling systems especially new generation vehicles.

Benefits

- Provides perfect protection of the engine cooling system against freezing, boiling, corrosion, rusting, cavitation and wearing out.
- It does not evaporate at radiator temperatures.
- For perfect performance, the cooling system should not be contaminated and there should be no leak.
- Only clean and clear water should be used.
- It might be added into the cooling system that contains ethylene based antifreeze.

Performance

Audi TL 774-C, BMW N 600 69.0, CAT SEBU 6250-12, Jenbacher, MAN 324 Type NF, MB 325.0, MTU MTL 5048, Opel, Porsche 774-C, Seat, Skoda, VW TL 774-C, ZF Intarder

Typical Specifications*

Density, 15°C, kg/liter	ASTM D4052	1,129
Freezing Point, °C, (%50 Antifreeze)	ASTM D1177	-38
Freezing Point, °C, (%33 Antifreeze)		-18
Boiling Point, °C, (%100)	ASTM D1120	174
pH, 20°C, (%100)	ASTM D1287	7,2
pH, 20°C, (%30)		8,4

* Values shown may differ between productions.

